

## Declaration of performance: No. **CPR-NO1/0303**

1. Unique identification code of the product-type: **Latelastic**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

### **SURFACE PROTECTION PRODUCT-COATING**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Internal and external tiling on floors and walls**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **Laticrete Nordic AS, Stanseveien 31, 0903 Oslo**      [www.laticrete.no](http://www.laticrete.no)
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:      **Sytem 2+ System 3 for reaction to fire**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**The notified body Sintef building and infrastructure No. 1071, performed the initial inspection of the manufacturing plant of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+ and issued the certificates of conformity of the factory production control No 1071-CPD-1674**  
**The notified testing laboratory MPA Dresden GmbH. No 0767, performed the determination of the class of reaction to fire on samples taken by the manufacturer, under system 3, and issued the report No. 2012-B-0952/08**
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance

<b>Essential characteristics</b>	<b>Performance</b>	<b>Harmonized technical specification</b>
<b>Permability to CO<sub>2</sub></b>	<b>Sd &gt; 50 M</b>	<b>EN 1504-2:2004</b>
<b>Water vapour permability:</b>	<b>Class 1</b>	
<b>Cappillary absorption and permability to water</b>	<b>&lt;0,1 kg M<sup>2</sup> h-0,5</b>	
<b>Adhesion strength by pull off test</b>	<b>≥0,8 N/mm<sup>2</sup></b>	
<b>Adhesion after thermal compatibility:</b>	<b>≥0,8 N/mm<sup>2</sup></b>	
<b>Freeze-thaw cycling</b>	<b>≥0,8 N/mm<sup>2</sup></b>	
<b>Crack bridging ability:</b>	<b>A3 (-30°)</b>	
<b>Reaction to fire:</b>	<b>Euroclass E</b>	
<b>Dangerous substances</b>	<b>See SDS</b>	

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Signed for and on behalf of the manufacturer by: **Morten Gaarud – Managing Director**

(name and function)

Oslo, 06/01/2014

  
.....(place and date of issue)  
(signature)

## CE MARKING according to CPR 305/2011 and EN 1504-2:2004

	 <b>Laticrete Nordic AS</b> Stanseveien 31, 0903 Oslo <a href="http://www.laticrete.no">www.laticrete.no</a>
<b>CPR-NO 1/0303</b> <b>EN 1504-2:2004</b> <b>Laticrete Latelastic</b> <b>SURFACE PROTECTION PRODUCT-COATING</b> 1,3 ingress protection 2,2 Moisture control 8,9 Increasing resistivity	
Permability to CO2 Water vapour permability: Cappillary absorption and permability to water Adhesion strength by pull off test Adhesion after thermal compatibility: Freeze-thaw cycling Crack bridging ability: Reaction to fire Dangerous substances	Sd > 50 M Class 1 <0,1 kg M <sup>2</sup> h-0,5 ≥0,8 N/mm <sup>2</sup> ≥0,8 N/mm <sup>2</sup> A3 (-30°) Euroclass E See SDS