

Declaration of performance: No. CPR-NO1/0204

1. Unique identification code of the product-type: **MØRTEL 226**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

CEMENTITIOUS SCREED MATERIAL (CT-C25-F5)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Cementitious screed material for internal and external use in floor construction

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **Laticrete Nordic AS, Stanseveien 31, 0903 Oslo** www.laticrete.no
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
No tasks for notified body
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{fl}	EN 13813:2002
Release of corrosive substances:	CT	
Water permeability:	NPD	
Water vapour permeability:	NPD	
Compressive strength:	C25	
Flexural strength:	F5	
Wear resistance:	NPD	
Sound insulation:	NPD	
Sound absorption:	NPD	
Thermal resistance:	NPD	
Chemical resistance:	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Signed for and on behalf of the manufacturer by: **Morten Gaarud – General Manager**
(name and function)

Oslo, 01/07/2013
(place and date of issue)

(signature)



CE MARKING according to CPR 305/2011 and EN 13813:2002

	 <p data-bbox="683 560 1054 656">Laticrete Nordic AS Stanseveien 31, 0903 Oslo www.laticrete.no</p>																						
<p data-bbox="759 685 794 712">13</p> <p data-bbox="671 732 882 761">CPR-NO1/0204</p> <p data-bbox="592 784 962 813">EN 13813:2002 CT-C25-F5</p> <p data-bbox="683 835 869 864">MØRTEL 226</p> <p data-bbox="352 884 1201 913"><i>Cementitious screed material for internal use in floor construction</i></p> <table data-bbox="320 972 917 1420"><tr><td>Reaction to fire:</td><td>A1_n</td></tr><tr><td>Release of corrosive substances:</td><td>CT</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Water vapour permeability:</td><td>NPD</td></tr><tr><td>Compressive strength:</td><td>C25</td></tr><tr><td>Flexural strength:</td><td>F5</td></tr><tr><td>Wear resistance:</td><td>NPD</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr></table>		Reaction to fire:	A1 _n	Release of corrosive substances:	CT	Water permeability:	NPD	Water vapour permeability:	NPD	Compressive strength:	C25	Flexural strength:	F5	Wear resistance:	NPD	Sound insulation:	NPD	Sound absorption:	NPD	Thermal resistance:	NPD	Chemical resistance:	NPD
Reaction to fire:	A1 _n																						
Release of corrosive substances:	CT																						
Water permeability:	NPD																						
Water vapour permeability:	NPD																						
Compressive strength:	C25																						
Flexural strength:	F5																						
Wear resistance:	NPD																						
Sound insulation:	NPD																						
Sound absorption:	NPD																						
Thermal resistance:	NPD																						
Chemical resistance:	NPD																						